



Office: 432.652.3172
 Fax: 432.652.3173

After Hours: 432.556.0200
 Email: info@wmoil.net

HYDROSET II

The Hydroset II is a hydraulic set, mechanically held dual string production packer run above a single string hydraulic set or wireline set seal bore packer. Its short length makes it ideal for deviated wells or doglegs. Because no tubing manipulation is required to set this packer, the well head can be installed and flanged up before setting. It is available with short or long string setting capabilities and a variety of tubing connections. It is also adaptable for submersible pump applications. The Hydroset II features a sequential upper slip release system designed to release each slip individually reducing the pull required to release the packer. Due to the angles on the upper slips and upper slip cage, slips release smoothly from the casing.



OD	Casing			Max OD of Tool IN	Long String		Short String	
	Weight LBS/FT	Min ID	Max ID		Connection BOX UP/ PIN DOWN	Mandrel ID	Connection BOX UP/ PIN DOWN	Seal Bore ID
5-1/2	14.0 - 20.0	4.778	5.012	4.625	1.900 NU 10 RD	1.500	1.660 NU 10 RD	1.375
7	26.0 - 32.0	6.094	6.276	5.935	2-3/8 EUE 8 RD	1.938	2-3/8 NU 10 RD	1.938
	17.0 - 26.0	6.276	6.538	6.000	2-3/8 NU 10 RD	1.938	2-3/8 NU 10 RD	1.938