



Office: 432.652.3172
 Fax: 432.652.3173

After Hours: 432.556.0200
 Email: info@wmoil.net

R-3 DOUBLE GRIP PACKER

The R-3 is a double grip, compression set, retrievable packer that is mostly used in production, stimulation and testing operations.

Features:

- Differential lock helps keep the by-pass closed and locked to the mandrel during high-pressure operations
- Automatically returns to run-in position when moved up the hole
- Hydraulic hold-down for differential pressure from below
- Long stroke mandrel simplifies circulation of fluids without releasing the packer
- Large by-pass allows speedy equalization of fluids
- Rocker type slips
- Standard right-hand set, optional left-hand set
- Large bore available (45RDL)
- Parts interchangeable with other manufacturers



Setting Procedure

The R-3 Double Grip Packer is run in with the by-pass valve in the open position to permit free circulation both through and around the packer. The packer should be run one foot below setting depth. To set the R-3, pick up the tubing to the desired setting position, rotate to the right, and then slack-off. The J-pin will move clear of the J-slot and the cone will move under the slips. Application of set-down weight, for standard packing element system (7,000 lb. for sizes 4 1/2 thru 5 1/2, 5,000 lb. for size 5 1/2 x 27/8, 9,000 lb. for size 7", 11,000 lb. for size 8 5/8, and 15,000 lb. for size 9 5/8) closes and seals the bypass valve, sets the slips, and packs-off the packing elements. The formation below the packer, which is now completely isolated from the annulus above, is accessible only through the tubing string.

Releasing Procedure

To release the packer, raise the tubing string the full length of the packer. When the J-pin of the bottom sub engages the slip stop ring (jay housing), the J-pin automatically moves into the running position. This allows the tool to be moved up or down the wellbore as necessary. When the tubing is raised to release the packer, the by-pass valve opens to permit circulation through and around the packer.

Casing		Packer			
OD	Weight LBS/FT	Min ID	Max ID	Max OD	Standard Thread Connections
4-1/2	9.5 - 13.5	3.920	4.090	3.771	2-3/8 EU 8RD
5	15.0 - 18.0	4.250	4.408	4.125	2-3/8 EU 8RD
	11.5 - 15.0	4.408	4.560	4.250	2-3/8 EU 8RD



Office: 432.652.3172
 Fax: 432.652.3173

After Hours: 432.556.0200
 Email: info@wmoil.net

R-3 DOUBLE GRIP PACKER CONT.

OD	Casing			Packer	
	Weight LBS/FT	Min ID	Max ID	Max OD	Standard Thread Connections
5-1/2	26.0	4.408	4.560	4.250	2-3/8 EU 8RD
	20.0 - 28.4	4.440	4.778	4.500	2-3/8 EU 8RD
	20.0 - 23.0	4.670	4.778	4.500	2-3/8 EU 8RD
	15.5 - 20.0	4.778	4.950	4.641	2-3/8 EU 8RD
	13.0 - 15.5	4.950	5.044	4.781	2-7/8 EU 8RD 2-3/8 EU 8RD
5-3/4	22.5	4.893	5.044	4.781	2-7/8 EU 8RD
		4.950	5.190	4.781	2-3/8 EU 8RD
6	26.0	4.893	5.044	4.781	2-7/8 EU 8RD
		4.950	5.190	4.781	2-3/8 EU 8RD
7	24.0	5.830	5.937	5.656	2-7/8 EU 8RD
	17.0 - 20.0	6.456	6.538	5.812	2-7/8 EU 8RD
	38.0	5.830	5.937	5.656	2-7/8 EU 8RD
	32.0 - 35.0	6.004	6.094	5.812	2-7/8 EU 8RD
	26.0 - 29.0	6.184	6.276	5.698	2-7/8 EU 8RD
	20.0 - 26.0	6.276	6.456	6.078	2-7/8 EU 8RD
	17.0 - 20.0	6.456	6.538	6.266	2-7/8 EU 8RD
7-5/8	33.7 - 39.0	6.625	6.765	6.453	2-7/8 EU 8RD
	24.0 - 29.7	6.875	7.025	6.672	2-7/8 EU 8RD
	20.0 - 24.0	7.025	7.125	6.812	2-7/8 EU 8RD
8-5/8	44.0 - 49.0	7.511	7.625	7.312	3-1/2 EU 8RD
9-5/8	47.0 - 53.5	8.535	8.681	8.218	3-1/2 EU 8RD
	40.0 - 47.0	8.681	8.835	8.437	3-1/2 EU 8RD
	29.3 - 36.0	8.921	9.063	8.593	3-1/2 EU 8RD