



Office: 432.652.3172  
 Fax: 432.652.3173

After Hours: 432.556.0200  
 Email: info@wmoil.net

# WR BRIDGE PLUG

The **WR Bridge Plug** is a wireline set, wireline retrieve, packer-type bridge plug capable of holding differential pressure from above or below. The WR Bridge Plug is used as a temporary bridge plug for acidizing, fracturing, cementing, casing pressure tests, wellhead replacement, and zone isolation. The WR Bridge Plug utilizes standard wireline or hydraulic setting tools.

Features:

- Wireline set/ wireline retrieve
- 10,000 PSI differential pressure rating above and below the plug
- Bi-directional slips
- Equalization feature prevents premature release against differential pressure



Casing				
Size IN	Weight LBS/FT	Recommended Hole Size IN	Tool OD IN	Top Connection
2-3/8	4.6 - 4.7	1.964 - 2.046	1.850	5/8-18 UNF PIN
2-7/8	6.4 - 6.5	2.990 - 3.068	2.250	5/8-18 UNF PIN
3-1/2	7.7 - 9.2	7.688 - 7.921	2.700	-
4-1/2	15.1	3.763 - 3.826	3.640	-
	9.5 - 13.5	3.920 - 4.090	3.750	-
5	15 - 18	4.276 - 4.408	4.125	-
	11.5 - 15	4.408 - 4.560	4.250	-
5-1/2	26	4.670 - 4.778	4.250	-
	20 - 23	4.154 - 4.276	4.500	-
	15.5 - 20	4.778 - 4.950	4.641	-
	13 - 15.5	4.950 - 5.190	4.781	-



Office: 432.652.3172

Fax: 432.652.3173

After Hours: 432.556.0200

Email: info@wmoil.net

# WR BRIDGE PLUG

Casing				
Size IN	Weight LBS/FT	Recommended Hole Size IN	Tool OD IN	Top Connection
6	26	4.950 - 5.190	5.062	-
	20 - 23	5.240 - 5.352	4.500	-
	15 - 18	5.424 - 5.524	5.157	-
6-5/8	34	5.561 - 5.609	5.406	-
	28 - 32	5.675 - 5.791	5.484	-
	17 - 24	5.921 - 6.135	5.781	-
	17 - 20	5.938 - 6.135	5.807	-
	24	5.830 - 5.920	5.656	-
7	38 - 40	5.830 - 5.920	5.656	-
	32 - 35	5.938 - 6.135	5.807	-
	29 - 32	6.094 - 6.184	5.928	-
	26 - 29	6.184 - 6.276	5.968	-
	23 - 26	6.276 - 6.366	6.078	-
	17 - 20	6.456 - 6.538	6.281	-
7-5/8	33.7 - 39	6.625 - 6.765	6.453	-
	24 - 29.7	6.875 - 7.025	6.672	-
	20 - 24	7.025 - 7.125	6.812	-
8-5/8	32 - 40	7.688 - 7.921	7.536	-
	24 - 32	7.921 - 8.097	7.731	-
9-5/8	47 - 53.5	8.343 - 8.681	8.223	-
	40 - 47	8.681 - 8.835	8.442	-
	29.3 - 36	8.836 - 9.063	8.598	-
10-3/4	65.7 - 73.2	9.406 - 9.660	9.161	-
11-3/4	54 - 65	10.682 - 10.880	10.505	-
13-3/8	85 - 98	11.937 - 12.159	11.692	-
	72 - 86	12.125 - 12.347	11.970	-
	48 - 61	12.515 - 12.715	12.270	-